This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM QR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

(11) International Publication Number:

MC, NL, PT, SE).

WO 99/13246

F16H 59/12, G05G 5/03, B60K 20/02

(43) International Publication Date:

18 March 1999 (18.03.99)

(21) International Application Number:

PCT/GB98/02710

A1

(22) International Filing Date:

9 September 1998 (09.09.98)

(30) Priority Data:

9718980.7

9 September 1997 (09.09.97)

GB

(71)(72) Applicant and Inventor: HOJIN, Naofumi [JP/GB]; 6 Barrow Elm Barns, Netherton, Near Quenington, Gloucester GL7 5DE (GB).

(74) Agent: ALLSOP, John, Rowland; MacLeod Allsop, Bledington Grounds, Bledington, Gloucestershire OX7 6XL (GB).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU,

(81) Designated States: AU, CA, JP, KR, US, European patent (AT,

(54) Title: AN INDICATION DEVICE FOR VEHICLE OPERATING CONDITIONS



(57) Abstract

This invention relates to vehicles and in particular to the means provided in vehicles which presently are limited to providing the driver with a visual indication of vehicle operating conditions such as engine revolutions and selected gear positions. The need for visual determination of an operating condition as is presently the case, requires the driver to divert attention from the road ahead. This, as well as being a safety hazard, can be a distinct driving disadvantage. Thus in situations such as Formula (I) racing, even a split second movement of the driver's eyes from the road could be critical from the point of view of winning the race. The invention deals with these problems by providing touch-tell indicators easily accessible by the driver's fingers when operating a floor mounted gear shift or a modern type of button arrangement provided on the steering wheel, which provide the driver with all the information necessary as to gear selection and/or engine revolutions without the need to visually ascertain these parameters from instrument dials.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	Fſ	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
ВВ	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BB	Belgium	GN	Guinea	MK	The former Yugoslav	. TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	. Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belanus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IТ	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

AN INDICATION DEVICE FOR VEHICLE OPERATING CONDITIONS

FIELD OF THE INVENTION

5

This invention relates to vehicles and particularly to the means provided in vehicles which give a visual indication to the driver of vehicle operating conditions such as engine revolutions and selected gear positions.

10

15

20

BACKGROUND OF THE INVENTION

In the case of engine revolutions such visual indication is by means of a tachometer or revolution counter provided on the instrument panel of the vehicle. In the case of selected gear position this has to be ascertained by glancing at the gear shift; in some cases such as in an automatic gear transmission system, gear selection is also displayed on the instrument panel.

Gear selection when driving, and engine revolutions generated in that gear selection, are important not only from the point of view of engine stress but also in terms of the economy of fuel consumption which has become a predominant concern in recent times.

In this connection some vehicles are equipped with "economy indicators" which again are only visually accessible on the instrument panel of the vehicle.

25

A visual determination of these parameters naturally acts to draw the attention of the driver from what he should mainly be doing, that is observing road conditions and taking appropriate action as a result of those observed conditions.

In the use of a standard automatic transmission system in a vehicle, the driver has occasion to select gear ranges other than provided by the normal drive position. This would occur for example on hills and while negotiating corners.

5

A fairly recent innovation in automatic transmission systems and now adopted widely in Formula I racing cars, is the provision of a gear shift in the form of a pair of spaced buttons on the steering wheel of the vehicle.

10

20

One of the buttons is used to shift to higher gears, the other to lower gears, than the one

actually in use, all movements selecting individual gears which are held by the system and

only change at the driver's choosing.

In effect this system equates to the conventional manual system but without the need to

15 actuate a clutch or move a gear lever.

Thus whereas in an ordinary automatic transmission system which has ranges which the driver is able to select, that is for example the drive or D range so that the transmission automatically selects the gears available say 1st to 5th gear and other selectable gear ranges, the new system selects individual gears in the gear range which are held until the driver wishes to change gear of his own volition.

Porsche Motor Cars have recently introduced the Typtronic® system which incorporates a

conventional automatic transmission gear shift and an extra facility which enables the driver

to select individual gears.

The extra facility is provided in two forms, one of them is the same as that used in Formula I cars as described above, the other incorporates a selector gate separate but situated next to the conventional system into which the gear selector lever is movable. In the gate

- 3 -

position the selector lever is pushed forward to go upwardly through the gears and pulled backwards to shift to lower gears.

As allued to earlier if a driver wishes to know which gear or gear range he is in while using these various systems, or to have knowledge of engine revolutions, he has to observe indicators for example on an instrument panel. This is particularly important in a racing car because knowledge of the gear position and engine revolutions is essential, for example when negotiating corners or ascending inclines which presently requires the driver to move his or her attention away from the road.

10

15

20

OBJECT OF THE INVENTION

It is an object of the invention to provide indication means for determining engine operating parameters such as energy revolutions and gear selection whereby the information needed to determine these parameters is by feel rather than by visual observation.

Thus the present invention envisages that information about gear selection and/or the number of engine revolutions determined by that gear selection are ascertained by touch and feel so that the driver does not have to divert his attention from the primary purpose of controlling the vehicle under specific driving conditions.

Thus information concerning vehicle operating parameters in accordance with the invention may be determined by the hand rather than the eye.

25

SUMMARY OF THE INVENTION

According to the invention there is provided an indicating device for a vehicle comprising indication means providing touch-tell information of a vehicle operating parameter such as engine revolutions and gear selection, and means for relaying information representative of said operating parameter to the indication means to activate the same such that the driver is informed, as by feel, of said operating parameter.

Advantageously the indication means is provided on the gear shift of the vehicle and is preferably in the form of depressible buttons on the handle of a floor mounted gear shift, the depressed position of each button being indicative of a particular vehicle operating parameter.

15 BRIEF DESCRIPTION OF THE DRAWINGS

Other features and advantages of the present invention will become apparent from the following description of the preferred embodiments taken with reference to the accompanying drawings wherein:

20

10

- Fig. 1 shows two forms of gear shift in present use modified in accordance with the invention;
- Fig. 2 is a part plan view of a steering wheel incorporating position indicators in accordance with the invention:
- 25 Fig. 3 shows the two forms of gear shift of Fig. 1 further modified in accordance with the invention;
 - Fig. 4 shows the same view as Fig. 2 further modified in accordance with the invention;
 - Fig. 5 is a side view of the head of a gear shift provided with an alternative form of indication means in accordance with the invention, and

- 5 -

Fig. 6 is a side view of a modified form of the indicating means shown in Fig. 5.

PREFERRED EMBODIMENTS OF THE INVENTION

5

In Fig. 1 the head 2 of a gear shift 1 for an automatic transmission having a range of five

gears, is provided with four depressible buttons B1, B2, B3 and B4 which can be engaged

respectively by the four fingers of the hand.

The buttons B1 through B4 may be activated through the on board computer system of the

vehicle (not described herein) which may be adapted to provide signals to operate the

buttons in response to gear changes in the automatic transmission.

In the D range which is the position selected when the driver wishes the car to operate

automatically through the gears, the buttons B are in an on position, that is they are

physically up.

If the driver selects for example the four gear range then button 84 is automatically

depressed and the driver can feel this when handling the head 2. When a different gear

range is selected, for example the three gear range, the buttons B4 and B3 are

automatically depressed and so on.

The same concept can be applied in the Typtronic® system as described earlier in this

disclosure.

25

15

20

In the form of this system employing a gate adjacent a conventional gear lever selector, the

depressible buttons will be provided on the lever itself as with the Fig. 1 embodiment and

activatable both for the conventional position of the gear lever where gear range selection

is possible and for individual gear selection with the gear lever selector in the gate position.

In the other form of the Typtronic® system as illustrated in Fig. 2, depressible buttons B are attached to the curve of the steering wheel W adjacent the higher and lower gear selection buttons 5, 6 provided on a spoke S of the steering wheel W, so as to be in easy reach of the driver's fingers when the shift is being used.

With this arrangement when operating the buttons 5, 6 the driver does not have to resort to any visual indication on an instrument panel as to any present gear position, rather he uses his fingers to determine operating conditions by finger searching the buttons B.

10

5

In Fig. 3 and 4 a further illustration is given of an arrangement of touch-tell movable buttons or switches for a five-gear automatic transmission system.

This arrangement, when compared to Figs 1 and 2, has an additional larger leverage button or pad D5 positioned so as to be length-wise of the straight line array of buttons numbered 1, 2, 3 and 4.

When the driver is in 4th gear only button pad D5 is activated to a depressed position while the rest of the buttons or switches 1 through 4 are in their up or rest position.

20

When the transmission is in 3rd gear the buttons or switches D5 and 4 are activated to their depressed positions and so on. In this case of course switches or buttons D5, 4, 3, 2 and 1 indicate a range of gear selection.

Thus when the driver starts the car, and chooses the first gear to move off or the system chooses the first gear automatically, all the remotely actuable touch-tell switches or buttons, with the exception of button 1, are in the up position.

- 7

When the car engages second gear the switches or buttons 2 and 1 are in the up position while the rest of the switches are depressed.

When the fifth gear is reached all the switches or buttons D5, 4, 3, 2 and 1 are in their rest positions.

The above touch-tell concept of providing information to a driver as to gear selection may also be used to provide the driver with knowledge of engine revolutions without the need for visual observation of a revolution counter on the instrument panel.

10

5

In Fig. 5 the head 7 of a gear shift is provided with a single button 8 which is set to activate when the engine has reached a stress condition, which is presently indicated by a red zone on standard revolution counters.

In Fig. 6 two depressible buttons 9, 10 are shown, the upper one 9 of which will be set to activate when the engine revolutions reach stress conditions and the lower button 10 to tell the driver that the vehicle is not being driven in a manner commensurate with the best fuel economy.

As will have been apparent from the foregoing it is evident that the invention provides means whereby the driver of a car is able to determine gear selection, engine revolutions and the like, through physical contact rather than through the provision of visual information. Thus the driver's attention is not distracted by the need to take his eyes off the road to determine a particular gear engaged which as well as diminishing the joy of sporty driving for example is also a safety hazard.

The proposed system in accordance with the invention, is also an aid to fuel economy because it can relay information to the driver concerning gear selection and fuel usage in a more positive and compelling manner than heretofore possible.

5

10

15

20

The above is only one preferred form of the invention and other ways may readily be devised for its realisation by those skilled in the art. The invention is thus not limited for example to depressible buttons for relaying the required information about gear selection. For example vibrating buttons could be used or other such coded indicating means which may be sensed by touch could be employed to achieve the required result all within the scope of the invention as defined in the appended claims.

Moreover the invention is equally applicable to manually operated gear transmissions as will be readily appreciated. In this connection, as with an automatic transmission system, and in relation to touch-tell determination of gear or gear range selection, actual movements of the gear shift be it floor mounted or positioned on the steering wheel, could be used by simple mechanical means to activate in the required sequence, the touch-tell buttons, all positioned within easy reach of the driver's fingers, in the embodiments described.

In relation to touch-tell determination of engine revolutions, the necessary signals to activate the buttons may be obtained from the on-board computer system of the vehicle although other methods to obtain those signals from the vehicle engine would be readily apparent to those skilled in the art. For example alarm buzzers presently exist to tell the driver when maximum engine revolutions have been reached and the same circuitry could be employed to activate the touch-tell buttons instead of the alarm.

CLAIMS

5

- An indicating device for a vehicle comprising indication means providing touch-tell information of a vehicle operating parameter such as engine revolutions and gear selection, and means for relaying information representative of said operating parameter to the indication means to activate the same such that the driver is informed, as by feel, of said operating parameter.
- An indicating device as claimed in claim 1 wherein the indication means is provided on a floor mounted gear shift of the vehicle.
 - An indicating device as claimed in claim 1 wherein the indication means is on the steering wheel of the vehicle.
- An indicating device as claimed in claim 1 wherein in the case of the vehicle being provided with a finger operable gear shift on the steering wheel, the indication means is positioned adjacent said finger operable gear shift for finger searching by the vehicle driver.
- An indicating device as claimed in any preceding claim wherein the touch-tell indication means is in the form of finger searchable actuable buttons, which actuate in a particular coded sequence in response to signals provided by an on-board computer system of the vehicle and representative of said operating parameter.
- An indicating device as claimed in claim 5 wherein a particular gear or gear range engaged is indicated by a depressed position of the buttons, the greater number of buttons depressed the lower the gear or the fewer the number of gears in the gear range selected, respectively.

An indicating device as claimed in claim 5 wherein there is a single depressible button on the gear shift or steering wheel respectively, said button being actuated to a depressed position when engine revolutions exceed a permitted number commensurate with allowable engine stress and/or economic fuel consumption.

5

8


An indicating device as claimed in claim 7 wherein there is a further depressible button on the gear shift or steering wheel respectively, said additional button moving to a depressed position when consumption of fuel exceeds a maximum predetermined value commensurate with economic fuel consumption.

10

An indicating device for a vehicle substantially as hereinbefore described with reference to and as illustrated in the accompanying drawings.

1/2

PCT/GB98/02710









FIG.2.












FIG.5.

INTERNATIONAL SEARCH REPORT

International application No. PCT/GB 98/02710

A. CLAS	A. CLASSIFICATION OF SUBJECT MATTER						
F 16	H 59/12,G 05 G 5/03,B 60 K	20/02					
According to	International Patent Classification (IPC) or to both r	national classification and IPC					
	OS SEARCHED						
	cumentation searched (classification system followed by	classification symbols)					
B 6	O K,F 16 H,G 05 G						
Documentation	on searched other than minimum documentation to the ex	tent that such documents are included in the	e fields searched				
	a base consulted during the international search (name of	Edata base and subara practicable rearch to	me used)				
Electronic da	a base consulted during the international search (name of	data vaso aid, where practicable, scator to	ans usory				
•							
C. DOCUM	MENTS CONSIDERED TO BE RELEVANT	T					
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.				
		7					
x ·	Patent Abstracts of Vol. 13, No. 454	1,2					
	13 October 1989;						
	& JP,A,01-177114 13 July 1989.	(SUZUKI),					
A	20 0,22		3-9				
A	DE 19510179 A1	-	1 0				
A	(MEYERLE) 28 Ser	otember 1995	1-9				
	(28.09.95), fig. 6a-6c.						
	- -	-					
х	Patent Abstracts of Vol. 96, No. 8,		1,2				
	1996;	Jo Magabe					
	& JP,A,08-091079 09 April 1996.	9 (KUBOTA)					
	09 April 1996.		3-9				
A	A		3 3				
X Furthe	r documents are listed in the continuation of Box C.	See patent family annex.					
* Special categories of cited documents: "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention							
to be of particular relevance "E" earlier document but published on or after the international filing date "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an invention cannot be considered novel or cannot be considered to involve an invention cannot be considered novel or cannot be conside							
cited to special	establish the publication date of another offation or other reason (as specified)	"Y" document of particular relevance; the	claimed invention cannot be				
"O" document referring to an oral disclosure, use, exhibition or other means considered to involve an inventive step when the documents with one or more other such documents, such to being obvious to a person skilled in the art							
"P" document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family							
Date of the actual completion of the international search Date of mailing of the international search report							
	30 November 1998	0 4, 02, 1999					
Name and r	nailing address of the ISA/	Authorized officer					
Europe	an Patent Office	WERDECKER 6	e.n.				
Facsimile N	lo.	Telephone No.					

INTERNATIONAL SEARCH REPORT

International application No.
PCT/GB 98/02710

		PCT/GB 9	8/02710
C (Continuatio	on). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant	Relevant to claim No.	
х	Patent Abstracts of Japan, Vol. 09, No. 152 (M-391), 27 June 1985; & JP,A,60-029336 (ISUZU),		1,2
A	14 February 1985.	3.0	
			3-9
		i	
		į	
	•		
1			
			•

ANHANG

ANNEX

ANNEXE

zum internationalen Recherchen-bericht über die internationale Patentanmeldung Nr.

to the International Search Report to the International Patent Application No.

au rapport de recherche inter-national relatif à la demande de brevet international n°

PCT/GB 98/02710 SAE 208263

In diesem Anhang sind die Mitglieder der Patentfamilien der im obenge- members relating to the patent documents nannten internationalen Recherchenbericht angeführten Patentdokumente angegeben. Diese Angaben dienen nur zur Uhter- richtung und erfolgen ohne Gewähr.

This Annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The Office is in no may liable for these particulars which are given merely for the purpose of information.

La presente annexe indique les membres de la famille de brevets relatifs aux documents de brevets cités dans le rapport de recherche international visée ci-dessus. Les reseignements fournis sont donnés à titre indicatif et n'engagent pas la responsibilité de l'Office.

la Recherchenberii angeführtes Patentdol Patent document c in search report Document de brevet i dans le rapport de re	kument Veröffentlichu ited Publication date cité Date de	ng Pater Pate nen Membre	led(er) der otfamilie ent family ober(s) e(s) de la e de brévets	Datum der Veröffentlichung Publication date Date de publication	
JF A2 11771	14 13-07-89	7 JP B2	2576558	29-01-97	
DE A1 195101	79 28-09-95		1953440003143388 19534440003143388 1953740003143388 19557600201143388 195601423114644 1976664003155 197666400315 197666400315 197666400315 197666400315 197666400315 197666400315 197666403 197666403 197666	29102524 12124 2910252 1214 1212 1212 1212 1212 1212 1212 1	·
JP A2 80910	79 09-04-96	b keine	- none -	rien	
JP A2 600293	36 14-02-85	5 keine	- none -	rien	